


# iBiotec®

TECHNICAL PRODUCTS OF VEGETABLE ORIGIN

FOR APPLYING

HOT, WARM, AND COLD ASPHALT



Datasheet - Last update: 2023/08/28

## iBiotec®

# SOLVETAL® 5050

ready-to-use

2 FUNCTIONS

DE-BITUMINIZING AND ANTI STICKY  
SPECIAL CONSTRUCTION SITE

Specific formula

not to degrade the coatings



**Improves safety at work**

**Made from new generation vegetable-based esters**

**Fully biodegradable**

**Use undiluted**

**Formula adapted to prevent damage to roadways under construction**

**DESCRIPTION**

**SOLVETAL® 5050** is a concentrated fluid for de-bituminizing and anti-sticking treatment, for the transport and application of road surfaces.

**SOLVETAL® 5050** is a cleaning fluid specifically developed to replace low flash point or smoke generating vegetable-based esters. It immediately meets the expectations of Branch Managers, Safety Coordinators and Operations and Site Managers, not only in terms of safety at work, hygiene and the environment, but also in terms of performance and compatibility with the equipment and its environment

**PHYSICAL AND CHEMICAL PROPERTIES**

PROPERTIES	STANDARDS	VALUES	UNITS
Appearance	Visual	Liquid	-
Solubility in water	-	0	%
Colour*	Visual	-	-
Odour	Olfactory	Weak	-
Density at 25°C	NF EN ISO 12185	895	kg/m <sup>3</sup>
Freezing point	ASTM D 97	-20	°C
Kinematic viscosity at 40°C	NF EN 3104	10.5	mm <sup>2</sup> /s
Refractive index	NF EN ISO 6320	1.4620	
<b>PERFORMANCE CHARACTERISTICS</b>			
PROPERTIES	STANDARDS	VALUES	UNITS
De-bituminizing time	Internal method	6'30"	mn.sec
Fuel oil de-bituminizing time	Internal method	5'45"	mn.sec
<b>FIRE SAFETY PROPERTIES</b>			
PROPERTIES	STANDARDS	VALUES	UNITS
Vacuum flash point	EN ISO 2592	194	°C
Self-ignition point	ASTM E 659	>300	°C
Lower explosive limit	-	Non-explosive	% (v/v)
Upper explosive limit	-	Non-explosive	% (v/v)
Vapour pressure	-	<0.01	kPa at 20°C
Content of explosive, oxidizing, flammable, highly or extremely flammable substances	EEC Regulation 1272/2008 CLP	Total absence	-
<b>TOXICOLOGICAL PROPERTIES</b>			
PROPERTIES	STANDARDS	VALUES	UNITS
Iodine value	NF EN 14111	<100	g/100 g
Totox (Anisidine Index + 2x Incide Peroxide)	-	48.56	-
Accelerated oxidability test (Rancimat test)	NF ISO 6886		
- Flow rate		10	L/h
- Temperature		100	°C
- Time		2.6	h
Content of toxic, very toxic, carcinogenic, mutagenic,	EEC Regulation	Total absence	-

reprotoxic, harmful, irritant or corrosive substances	1272/2008 CLP		
<b>ENVIRONMENTAL PROPERTIES</b>			
<b>PROPERTIES</b>	<b>STANDARDS</b>	<b>VALUES</b>	<b>UNITS</b>
Biodegradability	OECD TEST 301 B	Easily biodegradable	-
VOC (Volatile Organic Compounds) content	-	0	%
Solvent content	-	0	%
Environmentally hazardous substances content	EEC Regulation 1272/2008 CLP	Total absence	-

### PRECAUTIONS FOR USE

Store under cover in temperate environments before use.

Do not apply the product in large quantities or using a drum. Preferably use a sprayer.

In case of any accidental spillage on newly laid surfaces, rinse the surfaces immediately and thoroughly with water. The primary function of this product is to remove bitumen.

Do not apply to asphalt before and after laying.

Use undiluted. Do not mix with fuel oil, which is classified as carcinogenic.

Do not use as a bodywork detergent.

### APPLICATIONS

<b>FUNCTIONS</b>	<b>SUPPORTS (equipment or hardware) concerned</b>
De-bituminizing	<ul style="list-style-type: none"> <li>▶ Spreader booms and emulsion circuits for integrated boom finishers</li> <li>▶ Borders</li> <li>▶ Soiled tools (rake handles and teeth, shovels, etc.)</li> <li>▶ Soiled clothes</li> <li>▶ Soiled gloves</li> <li>▶ Soiled shoes</li> </ul>
Anti-stick	<ul style="list-style-type: none"> <li>▶ Finisher table</li> <li>▶ Profiler conveyor ledger</li> <li>▶ Finisher feeder and feed screw</li> <li>▶ Finisher belt</li> <li>▶ Loader buckets carrying asphalt</li> <li>▶ Sleds for CMA machines</li> <li>▶ Tools (scrapers, shovels, rakes, etc.)</li> <li>▶ Manhole top plates</li> <li>▶ Shoes</li> <li>▶ Vibrating plates</li> </ul>

### DIRECTIONS FOR USE

Spray a fine mist on the surfaces to be treated.

To remove asphalt deposits, leave for several minutes and then rinse with a high-pressure cleaner.

## PRESENTATIONS

### Container GRV 1000 L



### Drum 200 L



### Can 20 L



**iBiotec<sup>®</sup> Tec Industries<sup>®</sup>Service**  
Z.I La Massane - 13210 Saint-Rémy de Provence – France  
Tél. +33(0)4 90 92 74 70 – Fax. +33 (0)4 90 92 32 32  
[www.ibiotec.fr](http://www.ibiotec.fr)

USAGE RESERVE AUX UTILISATEURS PROFESSIONNELS  
Consulter la fiche de données de sécurité.

Les renseignements figurant sur ce document sont basés sur l'état actuel de nos connaissances relatives au produit concerné. Ils sont donnés de bonne foi. Les caractéristiques y figurant ne peuvent être en aucun cas considérées comme spécifications de vente. L'attention des utilisateurs est en outre attirée sur les risques éventuellement encourus lorsqu'un produit est utilisé à d'autres usages que ceux pour lequel il est conçu. Parallèlement, le client s'engage à accepter nos conditions générales de marché de fournitures dans leur totalité, et plus particulièrement la garantie et clause limitative et exonératoire de Responsabilité. Ce document correspond à des secrets commerciaux et industriels qui sont la propriété de Tec Industries Service et, constituant un élément valorisé de son actif, ne saurait être communiqué à des tiers en vertu de la loi du 11 juillet 1979.